

X-AIR Niedrigtemperatur-HK Austausch Leistungswerte in Watt bei 20° Raumtemperatur

Typ	Höhe (mm)	Länge (mm)	Silent-Komfort			Stufe 1/2/3			Silent Boost			Statischer Betrieb		
			45/35	40/35	35/30	45/35	40/35	35/30	45/35	40/35	35/30	45/35	40/35	35/30
22	550	600	478	409	277	344/426/478	292/364/409	193/244/277	527	452	307	291	244	155
22	550	800	638	546	369	458/568/638	389/485/546	258/326/369	702	602	410	388	325	207
22	550	1000	797	682	461	573/710/797	486/606/682	322/407/461	878	753	512	485	406	259
22	550	1200	956	818	553	688/852/956	583/727/818	386/488/553	1054	904	614	582	487	311
22	550	1400	1116	955	645	802/994/1116	680/848/955	451/570/645	1229	1054	717	679	568	363
22	550	1600	1275	1091	738	917/1136/1275	778/970/1091	515/651/738	1405	1205	819	776	650	414
22	550	1800	1435	1228	830	1031/1278/1435	875/1091/1228	580/733/830	1580	1355	922	873	731	466
22	550	2000	1594	1364	922	1146/1420/1594	972/1212/1364	644/814/922	1756	1506	1024	970	812	518
33	550	600	502	423	276	473/491/502	399/414/423	261/270/276	528	447	294	370	310	199
33	550	800	669	564	368	630/655/669	533/552/564	348/360/368	704	596	393	494	414	265
33	550	1000	836	706	459	788/818/836	788/818/836	666/690/706	880	745	491	617	517	331
33	550	1200	1004	847	551	945/982/1004	945/982/1004	799/829/847	1056	894	589	741	621	398
33	550	1400	1171	988	643	1103/1146/1171	1103/1146/1171	932/967/988	1232	1043	687	864	724	464
33	550	1600	1338	1129	735	1260/1309/1338	1260/1309/1338	1065/1105/1129	1407	1192	785	988	828	530
33	550	1800	1506	1270	827	1418/1473/1506	1418/1473/1506	1198/1243/1270	1583	1341	883	1111	931	596
33	550	2000	1673	1411	919	1576/1637/1673	1576/1637/1673	1331/1381/1411	1759	1490	981	1235	1035	663